


LED Strip Light SMD3528 L Dimming




LED Strip Light SMD3528




Product Dimensions:



Luminous Intensity Distribution Diagram:



Lux Distribution:



Manufacturing Quality Standard:

- ISO 9001:2008

LED Luminaire Standard:

- EN/IEC 60598-1
- EN/IEC 60598-2-1
- EN/IEC 60598-2-2
- EN/IEC 60529
- EN/IEC 62471-2
- IEC 62612
- EN/IEC 60968
- IEC 62560
- EN/IEC 60061-1
- EN 13032-1
- EN 13032-2
- EN/IEC 62471
- EN/IEC 60825
- EN 60061-1

Electronic Driver Standard:

- EN/IEC 61347-1
- EN/IEC 61347-2-13
- EN/IEC 62384
- EN/IEC 61000-3-2
- EN/IEC 61000-3-3
- EN/IEC 61547
- EN 55015(CISPR 15)

LED Module Standard:

- IEC 62031
- IEC 60838-2-2

RoHS Standard:

- EPA3050B
- EN 1122B
- IEC 62321
- EPA3052
- EPA3060A
- EPA7196A
- EPA3540C
- EPA8270D

LED Luminaire Performance:

- Switching cycle: 100,000x

LED Light Photometric Standard:

- CIE; TM14; LM-75; IES; LDT; CEN; CIB

www.celex-led.com

Features:

- Life of LED:50,000 hours
- UV and IR free
- Excellent cooling system
- Green and eco-friendly without mercury
- Energy-saving

Applications:

- Cove and contour
- Vehicle interiors
- Backlighting



Specifications:

Part No	Color	LED Q'ty	Power Conx.	Flux/m	Flux/Roll	View Angle	Size
CESL3528W-L	2700±200K	60PCS/M	30W/Roll	350lm	1750±50lm	110°±5°	5m/Roll
CESL3528N-L	4000±200K	60PCS/M	30W/Roll	380lm	1800±50lm	110°±5°	5m/Roll
CESL3528C-L	6000±200K	60PCS/M	30W/Roll	400lm	1950±50lm	110°±5°	5m/Roll
CESL3528R-L	Red (620-630nm)	60PCS/M	30W/Roll	100lm	500±30lm	110°±5°	5m/Roll
CESL3528Y-L	Yellow (584-595nm)	60PCS/M	30W/Roll	90lm	450±30lm	110°±5°	5m/Roll
CESL3528G-L	Green (512-530nm)	60PCS/M	30W/Roll	210lm	1050±30lm	110°±5°	5m/Roll
CESL3528B-L	Blue (460-475nm)	60PCS/M	30W/Roll	50lm	250±30lm	110°±5°	5m/Roll

Products Characteristic:

- Input Voltage: DC 12V
- Operating Temperature: -20°C ~ 50°C
- Color:White
- 50,000 hours (Ta=25°C)
- Dimming:0~10V
- Materials: Cu Base
- LED Type: SMD3528
- Dimension:5000*8*2.2mm
- Net weight:65g/m

Fixed mode

Fixer	15 PCS/Roll
Double-sided adhesive	3M double side adhesive tape

Dimming system connection

